

Specifications

Metro Electric – rectangular frame

Twin motor/Sturdy/Fast adjustment



Metro Electric rectangle base high 650mm stroke. The classy, modern Metro Electric Sit/Standbase has speed, high weight lift factor and stability. The unique nylon rollers and cogs make for silent movement. The stylish design incorporates extra stable 250mm wide legs.

NOTE: This model is the 650mm stroke. Lower 570mm stroke on indent only. Legs and feet are aluminium with 2 adjustable glides per foot. Supports and cross bars are steel powder coated. Metro Model has 2 drive units - 1 Master and 1 slave. Full assembly instructions with all necessary components and tools included.



Specifications:

Indoor use only
2 Motors: (1 master and 1 slave)
Height: 630mm -1280mm
Frame width: 1180-1700mm
Minimum top plate depth outside legs: 570mm
Foot length: 740mm
Stroke: 650mm
Leg width: 250mm
Capacity: Dynamic 100Kg; Static 140kg
Speed: 0 Kg 42mm/sec, 80 Kg 33mm/sec
Input power: 240v, 1.5A, 50/60Hz
Duty cycle: 10 % (1minute on, 9 minutes off)
Life Span: 3500 Cycles (10,000 cycles average use)
Noise level: <50 dB (A)
Carton weight: 30kg